



Underground Utility Tape



Table of Contents

Empire® Detectable Tape Specifications.....	Pg. 3
Empire® Non-Detectable Tape Specifications.....	Pg. 4-5
Empire® Custom Tape.....	Pg. 6
Telecommunication Utilities.....	Pg. 7
Electrical Utilities.....	Pg. 8
Gas Utilities.....	Pg. 9
Water Utilities.....	Pg. 10-11
Quick Reference Guide.....	Back Cover

PROTECT | IDENTIFY | DETECT

Underground Warning Tape is the **last line of defense** for your underground utility. Underground Tape helps **prevent accidental dig-ins** that result in loss of revenue, repair expense, or damage to life and property. It **alerts workers** of buried cables, pipes, and utilities buried below.

Empire warning tape, available in APWA standard colors, carries the **specific warning message needed to identify** the valuable cable or pipe buried beneath.



Empire® Tape is Manufactured in the USA at our plant in Mukwonago, WI using Lead Free, Environmentally Safe products guaranteed to give you maximum durability in the field.

Empire® Detectable Tape Specifications

MAGNATEC® PREMIUM DETECTABLE TAPE



Samples on pages 7-12

Feature	Method	Value (English)	Value (SI)
Overall Thickness	ASTM D-2103	5.0 mil (Nominal)	0.125 mm
Foil Thickness	ASTM D-2103	.35 mil	8.89 microns
Weight	ASTM D-2103	27.5 lbs / 1,000 ft ²	13.4 kg / 100 m ²
Tensile Strength	ASTM D-882	Length: 7,651 psi	Length: 52.8 Mpa
Elongation	ASTM D-882	Length: 89%	Length: 89%
Printability	ASTM D-2578		> 40 dynes
Plastic Density	ASTM D-792-08		1.119 g/cc



- Environmentally Safe
- Lead Free
- Maximum Strength
- Permanent Messaging
- Wear Resistant
- Detectable by Conductive and Inductive Methods

Available in: Blue, Green, Orange, Yellow, Red, Purple, Tan
Custom Options on Page 6

THORTEC™ PREMIUM REINFORCED DETECTABLE TAPE



Samples on page 9

Feature	Method	Value (English)	Value (SI)
Overall Thickness	ASTM D-2103	7.0 mil (Nominal)	0.175 mm (Nominal)
Foil Thickness	ASTM D-2103	.35 mil	8.89 microns
Weight	ASTM D-2103	34.21 lbs / 1,000 ft ²	16.70 kg / 100 m ²
Tensile Strength	ASTM D-882	Length: 12,000 psi	Length: 82.74 Mpa
Elongation	ASTM D-882	Length: 24%	Length: 24%
Printability	ASTM D-2578		> 40 dynes
Plastic Density	ASTM D-792-08		1.055 g/cc



- Environmentally Safe
- Lead Free
- Maximum Strength
- Permanent Messaging
- Wear Resistant
- Detectable by Conductive and Inductive Methods

Available in: Yellow
Custom Options on Page 6

Empire® Non-Detectable Tape Specifications

SHIELDTEC® STANDARD NON-DETECTABLE TAPE



Samples on pages 7-12

Feature	Method	Value (English)	Value (SI)
Overall Thickness	ASTM D-2103	4.0 mil (Nominal)	0.1 mm (Nominal)
Weight	ASTM D-2103	17.04 lbs / 1,000 ft ²	8.32 kg / 100 m ²
Tensile Strength	ASTM D-882	Length: 2,565 psi	Length: 17.7 Mpa
Elongation	ASTM D-882	Length: 492%	Length: 492%
Printability	ASTM D-2578		> 40 dynes
Plastic Density	ASTM D-792-08		.951 g/cc

Available in: Blue, Green, Orange, Yellow, Red, Purple
Custom Options on Page 6



- Environmentally Safe
- Lead Free
- Wear Resistant
- Permanent Messaging

DURATEC® PREMIUM REINFORCED NON-DETECTABLE TAPE



Samples on pages 7-9

Feature	Method	Value (English)	Value (SI)
Overall Thickness	ASTM D-2103	7.0 mil (Nominal)	0.175 mm (Nominal)
Weight	ASTM D-2103	22.46 lbs / 1,000 ft ²	10.97 kg / 100 m ²
Tensile Strength	ASTM D-882	Length: 10,620 psi	Length: 73.22 Mpa
Elongation	ASTM D-882	Length: 38%	Length: 38%
Printability	ASTM D-2578		> 40 dynes
Plastic Density	ASTM D-792-08		.692 g/cc

Available in: Orange, Yellow, Red
Custom Options on Page 6



- Environmentally Safe
- Lead Free
- Wear Resistant
- Permanent Messaging

TRIFLEX™ HEAVY DUTY STRETCH



Samples on page 7

Feature	Method	Value (English)	Value (SI)
Overall Thickness	ASTM D-2103	6.0 mil (Nominal)	0.150 mm (Nominal)
Weight	ASTM D-2103	26.78 lbs / 1,000 ft ²	13.08 kg/100 m ²
Tensile Strength	ASTM D-882	Length: 5,940 psi	Length: 40.95 Mpa
Elongation	ASTM D-882	Length: 946%	Length: 946%
Printability	ASTM D-2578		> 40 dynes
Plastic Density	ASTM D-792-08		.928 g/cc

Available in: Orange
Custom Options on Page 6



- Environmentally Safe
- Lead Free
- Wear Resistant
- Permanent Messaging

MEGASTRETCH™ HI-STRETCH



Samples on page 7

Feature	Method	Value (English)	Value (SI)
Overall Thickness	ASTM D-2103	4.0 mil (Nominal)	0.1 mm (Nominal)
Weight	ASTM D-2103	17.88 lbs / 1,000 ft ²	8.73 kg / 100 m ²
Tensile Strength	ASTM D-882	Length: 6,340 psi	Length: 43.71 Mpa
Elongation	ASTM D-882	Length: 867%	Length: 867%
Printability	ASTM D-2578		> 40 dynes
Plastic Density	ASTM D-792-08		.928 g/cc

Available in: Orange
Custom Options on Page 6



- Environmentally Safe
- Lead Free
- Wear Resistant
- Permanent Messaging

Empire® Custom Tape



Tape	Color	Size	Model Number
MAGNATEC® Premium Detectable	Striped in any color	2" x 1,000' 3" x 1,000' 6" x 1,000' 6" x 2,500'	MT21 MT31 MT61 MT62.5
THORTEC™ Reinforced Detectable	Striped in any color	6" x 1,000'	TT61
SHIELDTEC® Standard Non-Detectable	Red	3" x 1,000' 6" x 1,000'	STR31 STR61
	Orange	3" x 1,000' 6" x 1,000'	STO31 STO61
	Yellow	3" x 1,000' 6" x 1,000' 12" x 1,000' 24" x 1,000'	STY31 STY61 STY121 STY241
DURATEC® Reinforced Non-Detectable	Red	3" x 1,000' 6" x 1,000' 6" x 3,000'	DTR31 DTR61 DTR63
	Yellow	6" x 1,000'	DTY61
	Orange	3" x 6,000' 4" x 1,000' 4" x 6,000'	DTO36 DTO41 DTO46
TRIFLEX™ Heavy-Duty Stretch	Orange	3" x 6,000' 6" x 6,000' 3" x 1,000'	TF036 TF066 TF031
MEGASTRETCH™ Hi-Stretch	Orange	3" x 6,000' 6" x 6,000'	MS036 MS066

To order please contact customer service at orders@empirelevel.com

Telecommunication Utility Options

MAGNATEC®

Feature	Method (ASTM)	Value (English)	Value (SI)
Overall Thickness	D-2103	5.0 mil (Nominal)	0.125 mm (Nominal)
Foil Thickness	D-2103	.35 mil	8.89 microns
Weight	D-2103	27.5 lbs / 1,000 ft ²	13.4 kg / 100 m ²
Tensile Strength	D-882	Length: 7,651 psi	Length: 52.8 Mpa
Elongation	D-882	Length: 89%	Length: 89%
Printability	D-2578		> 40 dynes
Plastic Density	D-792-08		1.119 g/cc

“Caution Fiber Optic Cable Below”

Sizes Available	Model Number
3" x 1,000'	31-150
6" x 1,000'	31-151

SHIELDTEC®

Feature	Method (ASTM)	Value (English)	Value (SI)
Overall Thickness	D-2103	4.0 mil (Nominal)	0.1 mm (Nominal)
Weight	D-2103	17.04 lbs / 1,000 ft ²	8.32 kg / 100 m ²
Tensile Strength	D-882	Length: 2,565 psi	Length: 17.7 Mpa
Elongation	D-882	Length: 492%	Length: 492%
Printability	D-2578		> 40 dynes
Plastic Density	D-792-08		.951 g/cc

“Caution Fiber Optic Cable Buried Below”

Sizes Available	Model Number
3" x 1,000'	22-435

DURATEC®

Feature	Method (ASTM)	Value (English)	Value (SI)
Overall Thickness	D-2103	7.0 mil (Nominal)	0.175 mm (Nominal)
Weight	D-2103	22.46 lbs / 1,000 ft ²	10.97 kg / 100 m ²
Tensile Strength	D-882	Length: 10,620 psi	Length: 73.22 Mpa
Elongation	D-882	Length: 38%	Length: 38%
Printability	D-2578		> 40 dynes
Plastic Density	D-792-08		.692 g/cc

“Caution Fiber Optic Cable Buried Below”

Sizes Available	Model Number
3" x 6,000'	28-031

TRIFLEX™

Feature	Method (ASTM)	Value (English)	Value (SI)
Overall Thickness	D-2103	6.0 mil (Nominal)	0.150 mm (Nominal)
Weight	D-2103	26.78 lbs / 1,000 ft ²	13.08 kg / 100 m ²
Tensile Strength	D-882	Length: 5,940 psi	Length: 40.95 Mpa
Elongation	D-882	Length: 946%	Length: 946%
Printability	D-2578		> 40 dynes
Plastic Density	D-792-08		.928 g/cc

“Caution Fiber Optic Cable Buried Below”

Sizes Available	Model Number
3" x 6,000'	26-036

MEGASTRETCH™

Feature	Method (ASTM)	Value (English)	Value (SI)
Overall Thickness	D-2103	4.0 mil (Nominal)	0.1 mm (Nominal)
Weight	D-2103	17.88 lbs / 1,000 ft ²	8.73 kg / 100 m ²
Tensile Strength	D-882	Length: 6,340 psi	Length: 43.71 Mpa
Elongation	D-882	Length: 867%	Length: 867%
Printability	D-2578		> 40 dynes
Plastic Density	D-792-08		.928 g/cc

“Caution Fiber Optic Cable Buried Below”

Sizes Available	Model Number
3" x 6,000'	25-071

Electrical Utility Options

MAGNATEC®

Feature	Method (ASTM)	Value (English)	Value (SI)
Overall Thickness	D-2103	5.0 mil (Nominal)	0.125 mm (Nominal)
Foil Thickness	D-2103	.35 mil	8.89 microns
Weight	D-2103	27.5 lbs / 1,000 ft ²	13.4 kg / 100 m ²
Tensile Strength	D-882	Length: 7,651 psi	Length: 52.8 Mpa
Elongation	D-882	Length: 89%	Length: 89%
Printability	D-2578		> 40 dynes
Plastic Density	D-792-08		1.119 g/cc

“Caution Electric Line Below”

Sizes Available	Model Number
2" x 1,000'	31-106
3" x 1,000'	31-107
6" x 1,000'	31-109

SHIELDTEC®

Feature	Method (ASTM)	Value (English)	Value (SI)
Overall Thickness	D-2103	4.0 mil (Nominal)	0.1 mm (Nominal)
Weight	D-2103	17.04 lbs / 1,000 ft ²	8.32 kg / 100 m ²
Tensile Strength	D-882	Length: 2,565 psi	Length: 17.7 Mpa
Elongation	D-882	Length: 492%	Length: 492%
Printability	D-2578		> 40 dynes
Plastic Density	D-792-08		.951 g/cc

“Caution Electric Line Buried Below”

Sizes Available	Model Number
3" x 1,000'	22-126
6" x 1,000'	22-130
6" x 1,000' dispenser box	22-130DB

DURATEC®

Feature	Method (ASTM)	Value (English)	Value (SI)
Overall Thickness	D-2103	7.0 mil (Nominal)	0.175 mm (Nominal)
Weight	D-2103	22.46 lbs / 1,000 ft ²	10.97 kg / 100 m ²
Tensile Strength	D-882	Length: 10,620 psi	Length: 73.22 Mpa
Elongation	D-882	Length: 38%	Length: 38%
Printability	D-2578		> 40 dynes
Plastic Density	D-792-08		.692 g/cc

“Caution Electric Line Buried Below”

Sizes Available	Model Number
3" x 1,000'	71-061

SHIELDTEC®

Feature	Method (ASTM)	Value (English)	Value (SI)
Overall Thickness	D-2103	4.0 mil (Nominal)	0.1 mm (Nominal)
Weight	D-2103	17.04 lbs / 1,000 ft ²	8.32 kg / 100 m ²
Tensile Strength	D-882	Length: 2,565 psi	Length: 17.7 Mpa
Elongation	D-882	Length: 492%	Length: 492%
Printability	D-2578		> 40 dynes
Plastic Density	D-792-08		.951 g/cc

“Caution Electric Line Buried Below”

Sizes Available	Model Number
3" x 1,000'	22-202
6" x 1,000'	22-205

Gas Utility Options

MAGNATEC®

Feature	Method (ASTM)	Value (English)	Value (SI)
Overall Thickness	D-2103	5.0 mil (Nominal)	0.125 mm (Nominal)
Foil Thickness	D-2103	.35 mil	8.89 microns
Weight	D-2103	27.5 lbs / 1,000 ft ²	13.4 kg / 100 m ²
Tensile Strength	D-882	Length: 7,651 psi	Length: 52.8 Mpa
Elongation	D-882	Length: 89%	Length: 89%
Printability	D-2578		> 40 dynes
Plastic Density	D-792-08		1.119 g/cc

"Caution Gas Line Below"

Sizes Available	Model Number
2" x 1,000'	31-140
3" x 1,000'	31-141
6" x 1,000'	31-143

THORTEC™

Feature	Method (ASTM)	Value (English)	Value (SI)
Overall Thickness	D-2103	7.0 mil (Nominal)	0.175 mm (Nominal)
Foil Thickness	D-2103	.35 mil	8.89 microns
Weight	D-2103	34.21 lbs / 1,000 ft ²	16.70 kg / 100 m ²
Tensile Strength	D-882	Length: 12,000 psi	Length: 82.74 Mpa
Elongation	D-882	Length: 24%	Length: 24%
Printability	D-2578		> 40 dynes
Plastic Density	D-792-08		1.055 g/cc

"Caution Gas Line Below"

Sizes Available	Model Number
2" x 1,000'	38-027

MAGNATEC®

Feature	Method (ASTM)	Value (English)	Value (SI)
Overall Thickness	D-2103	5.0 mil (Nominal)	0.125 mm (Nominal)
Foil Thickness	D-2103	.35 mil	8.89 microns
Weight	D-2103	27.5 lbs / 1,000 ft ²	13.4 kg / 100 m ²
Tensile Strength	D-882	Length: 7,651 psi	Length: 52.8 Mpa
Elongation	D-882	Length: 89%	Length: 89%
Printability	D-2578		> 40 dynes
Plastic Density	D-792-08		1.119 g/cc

"Caution Oil Line Below"

Sizes Available	Model Number
2" x 1,000'	31-087

SHIELDTEC®

Feature	Method (ASTM)	Value (English)	Value (SI)
Overall Thickness	D-2103	4.0 mil (Nominal)	0.1 mm (Nominal)
Weight	D-2103	17.04 lbs / 1,000 ft ²	8.32 kg / 100 m ²
Tensile Strength	D-882	Length: 2,565 psi	Length: 17.7 Mpa
Elongation	D-882	Length: 492%	Length: 492%
Printability	D-2578		> 40 dynes
Plastic Density	D-792-08		.951 g/cc

"Caution Gas Line Buried Below"

Sizes Available	Model Number
3" x 1,000'	22-211
6" x 1,000'	22-214

DURATEC®

Feature	Method (ASTM)	Value (English)	Value (SI)
Overall Thickness	D-2103	7.0 mil (Nominal)	0.175 mm (Nominal)
Weight	D-2103	22.46 lbs / 1,000 ft ²	10.97 kg / 100 m ²
Tensile Strength	D-882	Length: 10,620 psi	Length: 73.22 Mpa
Elongation	D-882	Length: 38%	Length: 38%
Printability	D-2578		> 40 dynes
Plastic Density	D-792-08		.692 g/cc

"Caution Gas Line Buried Below"

Sizes Available	Model Number
3" x 1,000'	71-070

Water Utility Options

MAGNATEC®

Feature	Method (ASTM)	Value (English)	Value (SI)
Overall Thickness	D-2103	5.0 mil (Nominal)	0.125 mm (Nominal)
Foil Thickness	D-2103	.35 mil	8.89 microns
Weight	D-2103	27.5 lbs / 1,000 ft ²	13.4 kg / 100 m ²
Tensile Strength	D-882	Length: 7,651 psi	Length: 52.8 Mpa
Elongation	D-882	Length: 89%	Length: 89%
Printability	D-2578		> 40 dynes
Plastic Density	D-792-08		1.119 g/cc

“Caution Water Line Below”

Sizes Available	Model Number
2" x 1,000'	31-021
3" x 1,000'	31-022
6" x 1,000'	31-024

MAGNATEC®

Feature	Method (ASTM)	Value (English)	Value (SI)
Overall Thickness	D-2103	5.0 mil (Nominal)	0.125 mm (Nominal)
Foil Thickness	D-2103	.35 mil	8.89 microns
Weight	D-2103	27.5 lbs / 1,000 ft ²	13.4 kg / 100 m ²
Tensile Strength	D-882	Length: 7,651 psi	Length: 52.8 Mpa
Elongation	D-882	Length: 89%	Length: 89%
Printability	D-2578		> 40 dynes
Plastic Density	D-792-08		1.119 g/cc

“Caution Sewer Line Below”

Sizes Available	Model Number
2" x 1,000'	31-052
3" x 1,000'	31-053
6" x 1,000'	31-055

SHIELDTEC®

Feature	Method (ASTM)	Value (English)	Value (SI)
Overall Thickness	D-2103	4.0 mil (Nominal)	0.1 mm (Nominal)
Weight	D-2103	17.04 lbs / 1,000 ft ²	8.32 kg / 100 m ²
Tensile Strength	D-882	Length: 2,565 psi	Length: 17.7 Mpa
Elongation	D-882	Length: 492%	Length: 492%
Printability	D-2578		> 40 dynes
Plastic Density	D-792-08		.951 g/cc

“Caution Water Line Buried Below”

Sizes Available	Model Number
3" x 1,000'	22-018
6" x 1,000'	22-020
12" x 1,000'	22-021

SHIELDTEC®

Feature	Method (ASTM)	Value (English)	Value (SI)
Overall Thickness	D-2103	4.0 mil (Nominal)	0.1 mm (Nominal)
Weight	D-2103	17.04 lbs / 1,000 ft ²	8.32 kg / 100 m ²
Tensile Strength	D-882	Length: 2,565 psi	Length: 17.7 Mpa
Elongation	D-882	Length: 492%	Length: 492%
Printability	D-2578		> 40 dynes
Plastic Density	D-792-08		.951 g/cc

“Caution Sewer Line Buried Below”

Sizes Available	Model Number
3" x 1,000'	22-045
6" x 1,000'	22-047

MAGNATEC®

Feature	Method (ASTM)	Value (English)	Value (SI)
Overall Thickness	D-2103	5.0 mil (Nominal)	0.125 mm (Nominal)
Foil Thickness	D-2103	.35 mil	8.89 microns
Weight	D-2103	27.5 lbs / 1,000 ft ²	13.4 kg / 100 m ²
Tensile Strength	D-882	Length: 7,651 psi	Length: 52.8 Mpa
Elongation	D-882	Length: 89%	Length: 89%
Printability	D-2578		> 40 dynes
Plastic Density	D-792-08		1.119 g/cc

“Caution Reclaimed Water Line Below”

Sizes Available	Model Number
3" x 1,000'	31-100

SHIELDTEC®

Feature	Method (ASTM)	Value (English)	Value (SI)
Overall Thickness	D-2103	4.0 mil (Nominal)	0.1 mm (Nominal)
Weight	D-2103	17.04 lbs / 1,000 ft ²	8.32 kg / 100 m ²
Tensile Strength	D-882	Length: 2,565 psi	Length: 17.7 Mpa
Elongation	D-882	Length: 492%	Length: 492%
Printability	D-2578		> 40 dynes
Plastic Density	D-792-08		.951 g/cc

“Caution Reclaimed Water Do Not Drink”

Sizes Available	Model Number
3" x 1,000'	22-112

MAGNATEC®

Feature	Method (ASTM)	Value (English)	Value (SI)
Overall Thickness	D-2103	5.0 mil (Nominal)	0.125 mm (Nominal)
Foil Thickness	D-2103	.35 mil	8.89 microns
Weight	D-2103	27.5 lbs / 1,000 ft ²	13.4 kg / 100 m ²
Tensile Strength	D-882	Length: 7,651 psi	Length: 52.8 Mpa
Elongation	D-882	Length: 89%	Length: 89%
Printability	D-2578		> 40 dynes
Plastic Density	D-792-08		1.119 g/cc

“Caution Storm Drain Line Below”

Sizes Available	Model Number
3" x 1,000'	31-031

Utilities Available in	Tape Type	Sizes Available/ model #	Model #	Minimum Order Quantity	Page Number
Telecommunications					
"Caution Fiber Optic Cable Below"	MAGNATEC® Premium Detectable Tape	3" x 1,000'	31-150	1 roll	7
		6" x 1,000'	31-151	1 roll	
"Caution Fiber Optic Cable Buried Below"	SHIELDTEC® Standard Non-Detectable Tape	3" x 1,000'	22-435	1 roll	7
"Caution Fiber Optic Cable Buried Below"	DURATEC® Reinforced Non-Detectable Tape	3" x 6,000'	28-031	1 roll	7
"Caution Fiber Optic Cable Buried Below"	TRIFLEX™ Heavy Duty Stretch Tape	3" x 6,000'	26-036	1 roll	7
"Caution Fiber Optic Cable Buried Below"	MEGASTRETCH™ Hi-Stretch Tape	3" x 6,000'	25-071	1 roll	7
Electrical					
"Caution Electric Line Below"	MAGNATEC® Premium Detectable Tape	2" x 1,000'	31-106	1 roll	8
		3" x 1,000'	31-107	1 roll	
		6" x 1,000'	31-109	1 roll	
"Caution Electric Line Buried Below" - Yellow	SHIELDTEC® Standard Non-Detectable Tape	3" x 1,000'	22-202	1 roll	8
		6" x 1,000'	22-205	1 roll	
"Caution Electric Line Buried Below"	SHIELDTEC® Standard Non-Detectable Tape	3" x 1,000'	22-126	1 roll	8
		6" x 1,000'	22-130	1 roll	
		6" x 1,000' (Dispenser Box)	22-130DB	1 roll	
"Caution Electric Line Buried Below"	DURATEC® Reinforced Non-Detectable Tape	3" x 1,000'	71-061	1 roll	8
Gas					
"Caution Gas Line Below"	MAGNATEC® Premium Detectable Tape	2" x 1,000'	31-140	1 roll	9
		3" x 1,000'	31-141	1 roll	
		6" x 1,000'	31-143	1 roll	
"Caution Gas Line Below"	THORTEC™ Reinforced Detectable Tape	2" x 1,000'	38-027	1 roll	9
"Caution Gas Line Buried Below"	SHIELDTEC® Standard Non-Detectable Tape	3" x 1,000'	22-211	1 roll	9
		6" x 1,000'	22-214	1 roll	
"Caution Gas Line Buried Below"	DURATEC® Reinforced Non-Detectable Tape	3" x 1,000'	71-070	1 roll	9
Oil					
"Caution Oil Line Below"	MAGNATEC® Premium Detectable Tape	2" x 1,000'	31-087	1 roll	9
Water					
"Caution Water Line Below"	MAGNATEC® Premium Detectable Tape	2" x 1,000'	31-021	1 roll	10
		3" x 1,000'	31-022	1 roll	
		6" x 1,000'	31-024	1 roll	
"Caution Water Line Buried Below"	SHIELDTEC® Standard Non-Detectable Tape	3" x 1,000'	22-018	1 roll	10
		6" x 1,000'	22-020	1 roll	
		12" x 1,000'	22-021	1 roll	
Sewer					
"Caution Sewer Line Below"	MAGNATEC® Premium Detectable Tape	2" x 1,000'	31-052	1 roll	10
		3" x 1,000'	31-053	1 roll	
		6" x 1,000'	31-055	1 roll	
"Caution Sewer Line Buried Below"	SHIELDTEC® Standard Non-Detectable Tape	3" x 1,000'	22-045	1 roll	10
		6" x 1,000'	22-047	1 roll	
Reclaimed Water					
"Caution Reclaimed Water Line Below"	MAGNATEC® Premium Detectable Tape	3" x 1,000'	31-100	1 roll	11
"Caution Reclaimed Water Do Not Drink"	SHIELDTEC® Standard Non-Detectable Tape	3" x 1,000'	22-112	1 roll	11
Storm					
"Caution Storm Drain Line Below"	MAGNATEC® Premium Detectable Tape	3" x 1,000'	31-031	1 roll	11
Force Main					
"Caution Force Main Below"	MAGNATEC® Premium Detectable Tape	2" x 1,000'	31-122	1 roll	Not Shown
Joint Trench					
"Caution Joint Trench Buried Utilities"	SHIELDTEC® Standard Non-Detectable Tape	8" x 1,000'	22-753	1 roll	Not Shown
Custom					
CUSTOM TAPE - Striped (any color)	MAGNATEC® Premium Detectable Tape	2" x 1,000'	MT21	72 rolls	6
		3" x 1,000'	MT31	48 rolls	
		6" x 1,000'	MT61	24 rolls	
		6" x 2,500'	MT62.5	8 rolls	
CUSTOM TAPE - Orange	SHIELDTEC® Standard Non-Detectable Tape	3" x 1,000'	STO31	56 rolls	6
		6" x 1,000'	STO61	28 rolls	
CUSTOM TAPE - Red	SHIELDTEC® Standard Non-Detectable Tape	3" x 1,000'	STR31	56 rolls	6
		6" x 1,000'	STR61	28 rolls	
CUSTOM TAPE - Yellow	SHIELDTEC® Standard Non-Detectable Tape	3" x 1,000'	STY31	56 rolls	6
		6" x 1,000'	STY61	28 rolls	
		12" x 1,000'	STY121	28 rolls	
		24" x 1,000'	STY241	14 rolls	
CUSTOM TAPE - Striped (any color)	THORTEC™ Reinforced Detectable Tape	6" x 1,000'	TT61	24 rolls	6
CUSTOM TAPE - Red	DURATEC® Reinforced Non-Detectable Tape	3" x 1,000'	DTR31	96 rolls	6
		6" x 1,000'	DTR61	48 rolls	
		6" x 3,000'	DTR63	16 rolls	
CUSTOM TAPE - Yellow	DURATEC® Reinforced Non-Detectable Tape	6" x 1,000'	DTY61	48 rolls	6
		3" x 6,000'	DTO36	16 rolls	
CUSTOM TAPE - Orange	DURATEC® Reinforced Non-Detectable Tape	4" x 1,000'	DTO41	72 rolls	6
		4" x 6,000'	DTO46	12 rolls	
CUSTOM TAPE - Orange	TRIFLEX™ Heavy Duty Stretch Tape	3" x 1,000'	TF031	60 rolls	6
		3" x 6,000'	TF036	20 rolls	
		6" x 6,000'	TF066	10 rolls	
CUSTOM TAPE - Orange	MEGASTRETCH™ Hi-Stretch Tape	3" x 6,000'	MS036	20 rolls	6
		6" x 6,000'	MS066	10 rolls	